

CE

DECLARATION OF PERFORMANCE

No. ESHTP-STIC-memb According to Annex III of the Regulation (EU) No. 305/2011

Name of the product

Self Adhesive Elastomeric Bituminous Waterproofing Tape

1. Unique identification code of the product-type:

ESHATAPE (Polyester-Aluminum Top Finish)

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11 (4):

Batch number: see packaging of the product

- 3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: Cracks sealing or repair (patching) of existing waterproofing layers, Joints sealing between different materials, Construction joints or cracks, UV protection and waterproofing of metal and concrete pipes Joint Sealing in automotive sector (caravans, cars, trucks) Joints sealing in prefabricated structures, Joints sealing in marine & cargo boats
- 4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11 (5):

ALFA ALFA ENERGY SA Paralia Aspropyrgou Attikis 19300 Aspropyrgos, Athens - Greece

Company Certified by

- Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 (2): Not relevant
- 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 2+

EN ISO 9001: 2008 7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

EN 13707:2004+A2:2009: system 2+

The notified body TZUS, Technical &Test Institute for

CE

construction, Prague Performed the initial inspection of the manufacturing plant and of the factory production control and the continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued:

1020-CPR-010021423

Certificate of conformity of the factory production control

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant

ALFA ALFA ENERGY S.A

Offices - Production: Paralia Aspropyrgou, 193 00 Aspropyrgos Attikis Tel: 210-5518700 Fax: 210-5572974 Offices – Warehouse Thessaloniki: Ipirou 18, 570 09 Kalochori, Thessaloniki Tel: 2310-783725, Fax: 2310-783326 Offices – Warehouse SOFIA Bulgaria Kv.Drujba Tel: +3592 9791119, Fax:+3592 9791180 e-mail: info@esha.gr, www.esha.gr

REGISTER No. S.A.: 8088/03/B/86/63(06) & 121709007000



9. Declared performance

Technical Characteristics	Т*	Performance	Unit	Test Specification
Visible defects		No defects	-	EN 1850-1
Length	± 0,02	10	m	EN 1848-1
Width	-	10 to 50	cm	EN 1848-1
Straightness		Pass	mm/10 m	EN 1848-1
Thickness	2	1.5	mm	EN 1849-1
Tensile strength (Long/Trans)	>	200 / 200	N/50mm	EN 12311-1
Elongation (Long/Trans)	2	20 / 20	%	EN 12311-1
Flexibility at low temperature	≤	-40	°C	EN 1109
Watertightness		Pass (≥ 0,2 Mpa)	-	EN 14694
Dangerous substances (asbestos or coal tar)	-	Does Not Contain	-	EN 14695, §4,4



10. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point **4**.

Signed for and on behalf of the manufacturer by:

Elias Aloupis, Chemical Engineer Quality Control Manager

EN ISO 9001: 2008 EN ISO 14001: 2004

CE



ALFA ALFA ENERGY S.A Offices - Production: Paralia Aspropyrgou, 193 00 Aspropyrgos Attikis Tel: 210-5518700 Fax: 210-5572974 Offices – Warehouse Thessaloniki: Ipirou 18, 570 09 Kalochori, Thessaloniki Tel: 2310-783725, Fax: 2310-783326 Offices – Warehouse SOFIA Bulgaria Kv.Drujba Tel: +3592 9791119, Fax:+3592 9791180

e-mail: <u>info@esha.gr</u> , www.esha.gr REGISTER No. S.A.: 8088/03/B/86/63(06) & 121709007000