







ROOF DRAINS / LEAF & GRAVEL GRATES / ROOF AIRVENTS / PIPE FITTINGS / SPECIAL ACCESSORIES






PLASTIC ROOF DRAINS & DRAIN ACCESSORIES FOR BITUMINOUS WATERPROOFING SYSTEMS

NAME	PRODUCT DESCRIPTION	PACKING
<p>ANTI-BACK UP VERTICAL ROOF DRAIN WITH MESHED FLANGE</p> 	<ul style="list-style-type: none"> • Universal anti-backup roof drain is one of the best systems for connecting rainwater pipes and drains on flat roofs, gutters of multi-pitched roofs, and industrial buildings. • It is particularly suitable for use with all kinds of APP or SBS modified bituminous membranes as well as liquid bitumen coatings. • The drain is made from a special synthetic rubbers' compound designed to score high flexibility and resistance to UV rays, ozone and other atmospheric and chemical agents. • It can be used in a wide temperature range as it is extremely flexible at low temperatures and stable over time. • It consists of a truncated body available in various diameters solidly attached to the meshed flange (5 mm x 5 mm). The stem piece of the unit has two or more strategically placed circular ribs which face outwards, which, when forced into the drain pipe prevent backing-up and form a perfect seal. The seal rings are compressed upwards when inserted into the drainpipe, achieving optimal sealing with any type of pipe. • The passage of water vapor or backing up of liquids into the roof system and particularly into the insulation is thus eliminated. • Available in diameters of 60 mm, 80 mm, 90 mm and 100 mm 	<p>D 60 mm: 40 pieces/box</p> <p>D 80,90 or 100 mm: 25 pieces/box</p>




NAME	PRODUCT DESCRIPTION	PACKING
<p>90° ANGLED ROOF DRAIN WITH RECTANGULAR INTERSECTION</p> 	<ul style="list-style-type: none"> • 90° angled roof drain can be used either as an external or internal drain and especially for horizontal drains through thick outer walls. The unit is used in conjunction with bends or fittings having seal rings and thus the joint can be within the wall and the down pipe can be placed at a minimum distance from the wall. • It is particularly suitable for application with all kinds bituminous membranes APP SBS, spread bitumen. • The drain is made from a special 'synthetic rubbers' compound designed to score high flexibility and resistance to UV rays, ozone and other atmospheric and chemical agents. <p>Available in:</p> <ul style="list-style-type: none"> • Rectangular intersection of 100 mm x100 mm and length 425 mm. • Rectangular intersection of 65 mm x100 mm and length 425 mm. 	<p>20 pieces/box</p>
<p>CURVE Φ100 100x100</p> 	<ul style="list-style-type: none"> • Curve – fitting made of special 'synthetic rubbers' compound suitable for application with all kinds of bituminous membranes. Resistant to UV radiation and atmosphere chemical agents. • Final diameter:100mm • From drain pipe intersection of 100 mm x100 mm 	<p>20 pieces/box</p>
<p>CURVE Φ100 65x100</p> 	<ul style="list-style-type: none"> • Curve – fitting made of special 'synthetic rubbers' compound suitable for application with all kinds of bituminous membranes. Resistant to UV radiation and atmosphere chemical agents. • Final diameter: 100mm • For drain pipe intersection of 65 mm x100 mm 	<p>20 pieces/box</p>

PLASTIC LEAF & GRAVEL GRATES


NAME	PRODUCT DESCRIPTION	PACKING
<p>LEAF GRATE 4 POLES Φ60-110</p> 	<p>Leaf grate with 4 poles for roof drains from Φ60 -110</p>	<p>100 pieces/box</p>
<p>NEW LEAF GRATE Φ75-125</p> 	<p>Leaf-grate suitable for roof drains from Φ75 -125</p>	<p>50/100 pieces/box</p>
<p>LEAF GRAVEL Φ60-200</p> 	<p>Leaf-grate and/or gravel-grate suitable for roof drains from Φ60 - 200</p>	<p>50 pieces/box</p>




PLASTIC AIRVENTS FOR BITUMINOUS WATERPROOFING SYSTEMS

NAME	PRODUCT DESCRIPTION	PACKING
AIR VENT (L) FOR FLAT ROOFS 	<ul style="list-style-type: none"> • AirVent with specially designed flange for easy adhesion of bituminous waterproofing membranes, such as APP, SBS and roofs covered with hot bitumen. • It creates a most effective ventilation system, discharging steam build-up under waterproofing layers. • It does not reduce the water repellent capacity of either the prefabricated membranes or the bitumen covering or the insulation capacity of the waterproofing. If used carefully, by trained professionals, it prevents curling, topping-up of the waterproofing system and damp concentration in the insulation materials. • It is made from a special 'synthetic rubbers' compound designed to score high flexibility and resistance to UV rays, ozone and other atmospheric and chemical agents. • It can be used in a wide temperature range as it is extremely flexible at low temperatures and stable over time. • Height: 270 mm 	<p>25 pieces/box</p>

PLASTIC PIPE / CABLE FITTINGS FOR BITUMINOUS WATERPROOFING SYSTEMS

NAME	PRODUCT DESCRIPTION	PACKING
POLYETH. PIPE FITTING 	<ul style="list-style-type: none"> • Special accessory for waterproofing around pipes and cables that penetrate bituminous waterproofing layers. • Available in diameters of Φ 50 - 90 mm and Φ 20 - 50 mm 	<p>Φ 50 – 90 mm: 20 pieces/box</p> <p>Φ 20 - 50 mm: 30 pieces/box</p>

PLASTIC BASES FOR PREFABRICATED SLABS

NAME	PRODUCT DESCRIPTION	PACKING
BASE FOR SLABS 15 mm WITH HOLE 	<ul style="list-style-type: none"> • Plastic Bases for prefabricated slabs quickly and easily resolve problems arising from the installation of a paving system. • They are placed directly on to the waterproofing cap sheet. The paving slabs are then placed directly onto them without the use of concrete or adhesives of any sort. • They are made of HDPE and their shape allow rainwater to drain and flow off easily on the underlying waterproofing membrane, thus also eliminating any chance of ponding caused by the supports themselves trapping water. • They are modular and can be stacked so as to achieve the height or thickness of gap underneath the paving desired, and eliminating any unevenness of the roof deck itself. • The plastic bases are divided and their height is 15mm 	<p>250 pieces/box</p>

The information contained in this leaflet is, to the best of our knowledge, true and reliable and is supported by the present state of our knowledge. According to the care taken and the method of application, upon which we have no influence, the values are subject to divergence. Therefore for best results, prior to use, an application test should be made by the user under his own processing conditions.

Alfa-Alfa Energy S.A.
 ATHENS/CENTRAL OFFICES-FACTORY: Aspropyrgos Beach, 193 00 Aspropyrgos, Attica
 T +30 2105518700, F +30 2105572974 | SALONICA/OFFICES-WAREHOUSE: 18 Epirou Street,
 570 09 Kalochori, Salonica, T+30 2310783725, F +30 2310783326 | www.eshagr.com • info@eshagr.com



EN ISO 9001:2008
 Cert. No. 605/D/2010



EN ISO 14001:2004
 Cert. No. EN 67/P/2010